## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: ELV

Supplier's address: ELV Info, Maiburger Straße 29-36, 26789 Leer, DE

## Model identifier: 109902 - LED-Lupenleuchte

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS	
Light source cap-type	LED			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	Yes			
Anti-glare shield:	Yes	Dimmable:	No	
Product parameters				

General product paraEnergy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer10EUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)730 in Wide cone (120°)C(90°)000(90°)000On-mode expressed in W(Pon), expressed in W10,0Si	Parameter ameters: Energy efficiency class Correlated colour counded to the nearest 100 K, for the range of correlated colour comperatures, rounded to the nearest 100 K, that can be set	Value F 6 500
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (P <sub>on</sub> ), 10,0 Si expressed in W	Energy efficiency class Correlated colour cemperature, rounded to the nearest 100 K, for the range of correlated colour cemperatures, rounded to the nearest 100 K, that	
mode(kWh/1000 h), rounded up to the nearest integerclUseful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)730 in Wide cone (120°)C(90°)ornn(90°)ororor <td>Class Correlated colour comperature, rounded to the nearest 100 K, for the range of correlated colour comperatures, rounded to the nearest 100 K, that</td> <td></td>	Class Correlated colour comperature, rounded to the nearest 100 K, for the range of correlated colour comperatures, rounded to the nearest 100 K, that	
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (P <sub>on</sub> ), 10,0 Si expressed in W	emperature, rounded to the nearest 100 K, or the range of correlated colour emperatures, rounded to the nearest 100 K, that	6 500
expressed in W ex	Lan be set	
	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
for CLS, expressed in W and rounded to the second decimal o va	Colour rendering ndex, rounded to the nearest integer, for the range of CRI- values that can be set	80
Outer Height 480 S	Spectral power	See image
dimensions Width 780 d	distribution in the	in last page
without Depth 220		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,313 0,337		
Parameters for directional light sources:					
Peak luminous intensity (cd)	350	Beam angle in degrees, or the range of beam angles that can be set	120		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	18	Survival factor	0,90		
the lumen maintenance factor	0,96				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9		

(a)'-' : not applicable;

(b)'-' : not applicable;

