Quick reference MA10200 Thermo- hygrometer sensor



MOBILE-ALERTS Sensor

This is a sensor for the "MOBILE-ALERTS" system, it can be used with this system only. To use the sensor you need a MOBILE-ALERTS gateway.

Sensor set up

Open the battery compartment of the temperature sensor and put in 2x AA batteries with the correct polarity.

Add Sensor

Open the app, dashboard is displayed. Tap "Add new sensor" and scan the QR code on the back of the temperature sensor. Then set a name for the sensor.

Specifications Batteries:

2 xMignon(LR06, AA) alkaline

approx. 2 years

Battery life: Measuring range temperature: -39.9℃ to +59.9℃

1 °C Accuracy: Measuring range humidity: 20-99%

Accuracy: 5%

Measurement intervals: 7 minutes Transmission range: 100m (open area) Frequency: 868 3 MHz

More information and detailed instructions can be found in the app at "Info" or at www.elv.com



Article: 117583

FLV Flektronik AG - Postfach 1000 - D-26787 Leer Telefon 0491/6008-88 - Telefax 0491/6008-244

eQ-3 Entwicklung GmbH Mailburger Str.36 26789 Leer



Old batteries do not belong into general household waste. You are obliged to return used batteries to your vendor or collection points.



Electrical devices have to be disposed separately from the general household waste. Take your old electronics to your local waste

collection point or recycling centre.